

SPECIFICATION

Style number:	UL2651	Document Number	Made date	Rev.
Specification:	26AWGxPH1.27	WCH14012608	2014-01-26	1.0V
Cross Section	<p style="text-align: center;">红边</p> <p style="text-align: center;">AWM 2651 26AWG 105°C 300V VW 1</p> <p style="text-align: center;">$1.05 \pm 0.08\text{mm}$</p> <p style="text-align: center;">$PH1.27\text{mm}$</p> <p style="text-align: center;">$PT*PH \pm 0.50\text{mm}$</p>			
Technical Parameters				
Conductor	Conductor Gauge (AWG)	26		
	Material	Tinned Stranded Copper		
	Configuration (mm)	TS7/0.16±0.007		
Insulation	Ave Thickness (mm)	0.26		
	Min Thickness (mm)	0.23		
	Over Diameter (mm)	1.05 ± 0.08		
	Pitch Distance (mm)	1.27		
	Width (mm)	$N*PH \pm 0.50$		
	Minimum Pins Quantity	2 Pins		
	Maximum Pins Quantity	34 Pins		
	Material	38P PVC (RoHS)		
Colour	Gray + Red Mark(1C)			
Electrical Capability	Rated Temperature (°C)	105		
	Rated Voltage (V)	300		
	Cond. Resistance ($\Omega/\text{KM } 20^\circ\text{C}$)	150		
	Insu. Resistance ($\text{M}\Omega/\text{KM } 20^\circ\text{C}$)	10		
Physical Characters	Flame Test	VW-1, FT1		
Marking	As per standard of UL2651			

